

# HEATY COMPLETE FIX LED-SERIES

Replenishment solution for systems from 400 litres



## Technical data

Art.-No. 100345  
Art.-No. 100345-OFK

Max. filling capacity*	360 l/h
Max. Operating pressure	8 bar
Max. Operating temperature	50 °C
Height / width in mm	630 / 550
Weight (approx.)	8.3 kg
Mixed bed capacity	6 l
Capacity at 420 µS/cm to < 100**	900 l
Power connection required	Yes, for LED

## Heaty Complete Fix Mini LED + OFK

The **Heaty Complete Fix LED series** is a completely pre-assembled replenishment unit! It is used if the system is larger than 400 litres and no system separator is available on site.

## Including

- Replenishment cartridge (composite of the Fix series)
- BA filling combination (except OFK)
- Water meter, shut-off devices
- Screen seal against resin ingress
- LED measuring cell
- Pressure-independent flow limiter

## Your advantages

- ✓ Ideal for large filling volumes from 400 litres
- ✓ Compliance with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1
- ✓ Simple handling
- ✓ Safety through LED measurement



\* Dependent on system and mains pressure.

\*\* The capacity specifications are based on the ideal case. Deviations may occur due to application errors, water quality and temperature.



# HEATY COMPLETE FIX LED-SERIES

Replenishment solution for systems from 400 litres



## Technical data

Art.-No. 100346  
Art.-No. 100346-OFK

Max. filling capacity*	600 l/h
Max. Operating pressure	8 bar
Max. Operating temperature	50 °C
Height / width in mm	600 / 550
Weight (approx.)	11.3 kg
Mixed bed capacity	9.5 l
Capacity at 420 µS/cm to < 100**	1,425 l
Power connection required	Yes, for LED

## Heaty Complete Fix Small LED + OFK

The **Heaty Complete Fix LED series** is a completely pre-assembled replenishment unit! It is used if the system is larger than 400 litres and no system separator is available on site.

## Including

- Replenishment cartridge (composite of the Fix series)
- BA filling combination (except OFK)
- Water meter, shut-off devices
- Screen seal against resin ingress
- LED measuring cell
- Pressure-independent flow limiter

## Your advantages

- ✓ Ideal for large filling volumes from 400 litres
- ✓ Compliance with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1
- ✓ Simple handling
- ✓ Safety through LED measurement



\* Dependent on system and mains pressure.

\*\* The capacity specifications are based on the ideal case. Deviations may occur due to application errors, water quality and temperature.



# HEATY COMPLETE FIX LED-SERIES

Replenishment solution for systems from 400 litres



## Technical data

Art.-No. 100347  
Art.-No. 100347-OFK

Max. filling capacity*	1,200 l/h
Max. Operating pressure	8 bar
Max. Operating temperature	50 °C
Height / width in mm	750 / 550
Weight (approx.)	20.6 kg
Mixed bed capacity	23 l
Capacity at 420 µS/cm to < 100**	3,450 l
Power connection required	Yes, for LED

## Heaty Complete Fix Big LED + OFK

The **Heaty Complete Fix LED series** is a completely pre-assembled replenishment unit! It is used if the system is larger than 400 litres and no system separator is available on site.

## Including

- Replenishment cartridge (composite of the Fix series)
- BA filling combination (except OFK)
- Water meter, shut-off devices
- Screen seal against resin ingress
- LED measuring cell
- Pressure-independent flow limiter

## Your advantages

- ✓ Ideal for large filling volumes from 400 litres
- ✓ Compliance with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1
- ✓ Simple handling
- ✓ Safety through LED measurement



\* Dependent on system and mains pressure.

\*\* The capacity specifications are based on the ideal case. Deviations may occur due to application errors, water quality and temperature.



# HEATY COMPLETE FIX LED-SERIES

Replenishment solution for systems from 400 litres



## Technical data

Art.-No. 100348  
Art.-No. 100348-OFK

Max. filling capacity*	2,400 l/h
Max. Operating pressure	8 bar
Max. Operating temperature	50 °C
Height / width in mm	1,280 / 550
Weight (approx.)	37.4 kg
Mixed bed capacity	46 l
Capacity at 420 µS/cm to < 100**	6,900 l
Power connection required	Yes, for LED

## Heaty Complete Fix Tall LED + OFK

The **Heaty Complete Fix LED series** is a completely pre-assembled replenishment unit! It is used if the system is larger than 400 litres and no system separator is available on site.

## Including

- Replenishment cartridge (composite of the Fix series)
- BA filling combination (except OFK)
- Water meter, shut-off devices
- Screen seal against resin ingress
- LED measuring cell
- Pressure-independent flow limiter

## Your advantages

- ✓ Ideal for large filling volumes from 400 litres
- ✓ Compliance with VDI 2035, ÖNORM H 5195-1 and SWKI BT 102-1
- ✓ Simple handling
- ✓ Safety through LED measurement



\* Dependent on system and mains pressure.

\*\* The capacity specifications are based on the ideal case. Deviations may occur due to application errors, water quality and temperature.

